

### Ring Torsion Load Cell



#### DESCRIPTION

The RLC is a low profile, high performance stainless steel ring torsion type load cell. The fully welded construction and glass-to-metal cable-entry ensure that this product can be used successfully in harsh environments found in the food, chemical and allied process industries. This product is suitable for small and medium platform scales, hoppers and process weighing. This product meets the stringent Weights and Measures requirements throughout Europe and USA.

#### FEATURES

- Capacity range: 250kg to 60 ton
- Low profile, stainless steel construction
- Hermetically sealed, IP66/68
- Meets OIML R-60 and NTEP 6000d
- Outputs are matched to ensure easy and accurate parallel connection of multiple load cells

#### OPTIONAL FEATURES

- ATEX certified versions are available for use in potentially explosive atmospheres
- Multi-interval and multiple-range versions are available

#### APPLICATIONS

- Platform scales
- Belt scales
- Silo hopper weighing

OUTLINE DIMENSIONS in millimeters									
CAPACITY (t)	0.25, 0.5, 1	2, 3.5, 5	10	Cable specifications:			CAPACITY (t)	28	60
A	1.0	6.0	-	Cable length: 3m for 0.25 - 1t, 5m for 3 - 10t, 10m for 28t, 15m for 60t			A	21	28
B	15.0	20.0	14.8	Excitation + Pink			B	46	62
C	25.0	30.0	35.0	Excitation - Grey			C	35.9	47.9
D	9.5	8.5	10.0	Output + Brown			D	120	140
E	M10	15 H7	Ø24.9	Output - White			R	400	600
F	Ø19	Ø19	Ø29.1	Cable screen is connected to load cell body. For capacities 28 & 60 ton cable screen is not connected to body.					
G	Ø25	Ø25	-						
H	M6 (3X120°) 8 Deep								
I	Ø70	Ø70	Ø83						
J	Ø80	Ø80	Ø95						
K	97.5	97.5	112.5						

SPECIFICATIONS					
PARAMETER	VALUE				UNIT
Standard capacities ( $E_{max}$ )	0.25, 0.5, 1, 2, 3.5, 5, 10, 28, 60				ton
Accuracy class according to OIML /	NTEP III L	D3	C3 <sup>(3)</sup>	C6 <sup>(2)</sup>	
Maximum no. of verification intervals (n <sub>lc</sub> )	10000		3000	6000	
Minimum verification interval			$E_{max}/10000$	$E_{max}/15000$	
Minimum verification interval type MR			$E_{max}/20000$ <sup>(1)</sup>	$E_{max}/28000$	
Rated output (=S)	2 (1.75 for 0.25t, 2.05 for 10t)				mV/V
Output accuracy for multiple LC systems	0.01				±mV/V
Zero balance	1.0				±% FSO
Combined error	0.0200	0.0300	0.0230	0.0115	±% FSO
Creep error (30 minutes)			0.0245	0.0123	±% FSO
Temperature effect on zero	(0.0010)	(0.0010)	0.0070	0.0045	±% FSO/5°C (°F)
Temperature effect on sensitivity (output)	(0.0008)	(0.0008)	0.0050	0.0025	±% FSO/5°C (°F)
Minimum dead load	0				%E <sub>max</sub>
Maximum safe over load	150				%E <sub>max</sub>
Ultimate over load	300				%E <sub>max</sub>
Maximum safe side load	100% up to 10 ton 50% for 28 & 60 ton				%E <sub>max</sub>
Deflection at E <sub>max</sub>	0.12 - 0.20				mm
Excitation voltage	5 to 15				V
Maximum excitation voltage	30				V
Input resistance	1110±50 (1100±50 for 0.25t & 10t) 1075±100 for 28t 1350±100 for 60t				Ω
Output resistance	1025±25 (1025±50 for 0.25t & 10t) 930±0.5 for 28t 1175±0.5 for 60t				Ω
Insulation resistance	≥5000 (20 for 28 & 60 ton)				MΩ
Compensated temperature range	-10 to +40				°C
Operating temperature range	-30 to +70				°C
Storage temperature range	-50 to +80				°C
Element material (DIN)	Stainless steel 1.4542				
Sealing (DIN 40.050 / EN60.529)	IP66 and IP68				
Recommended torque on fixation bolts	12 to 14				N*m
ATEX opt. for potent. explosive atmospheres	II2G EEx ib IIC T4/T6, II2D, IIID T70 II3G nA II T4/T6				

**Notes**

- (1) Capacities of 28 & 60 ton  $E_{max}/15,000$   
 (2) 250kg and 10 ton capacities are approved to OIML C3 only  
 Maximum application range for 0.5t is  $0.75 \cdot E_{max}$   
 (3) The following accuracy classes are available (from 0.5t to 10t): C3MI6 and C3MI7.5  
 Minimum dead load output return is  $\frac{1}{2} E_{max}/6000$  &  $\frac{1}{2} E_{max}/7500$  respectively

FSO - Full Scale Output

## Disclaimer

ALL PRODUCTS, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE.

Vishay Precision Group, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay Precision Group"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

The product specifications do not expand or otherwise modify Vishay Precision Group's terms and conditions of purchase, including but not limited to, the warranty expressed therein.

Vishay Precision Group makes no warranty, representation or guarantee other than as set forth in the terms and conditions of purchase. **To the maximum extent permitted by applicable law, Vishay Precision Group disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.**

Information provided in datasheets and/or specifications may vary from actual results in different applications and performance may vary over time. Statements regarding the suitability of products for certain types of applications are based on Vishay Precision Group's knowledge of typical requirements that are often placed on Vishay Precision Group products. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application.

No license, express, implied, or otherwise, to any intellectual property rights is granted by this document, or by any conduct of Vishay Precision Group.

The products shown herein are not designed for use in life-saving or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay Precision Group products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay Precision Group for any damages arising or resulting from such use or sale. Please contact authorized Vishay Precision Group personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.